



Vertical Mare Downlight with Glass




Technical Drawing



Light Distribution Curve



Standards of Application



Mechanical Specifications

+ Electrostatic powder coated aluminium frame/Stainless steel latches holding the reflector in the center of the luminaire. Suitable for installation in ceiling tiles and drywall ceiling system

Optical Specifications

+ High pure aluminium reflector" maintaining its optical properties, non-yellowing and non-discolouring throughout lifetime of the luminaire.

Technical & Electrical Specifications

- Control gear in a separate box or integrated for 1/13-26W (TC-DEL).
- Connection for operation on 220V-50Hz with conventional ballast and power factor correction capacitor (lamp TC-D).
- Connection for operation on 220V-50/60Hz with electronic ballast.
- Connection for operation with electronic dimmable ballast.
- Connection for emergency lighting system.
- The above luminaire is available for fluorescent compact lamps (E27) max.23W.
- The above luminaire is available for LED Bulbs.

Options

- Connection for emergency lighting system.
- Mirror or Matt Reflector
- Eco model is not including top box

Fields of Application



Product Details

Order Code (FL)	Order Code (LED Bulb)	Type	Power (W)	Lamp Type	Power Factor	Dimensions (mm) Ø h	Base (mm)	Base	Pcs/Pack
CST 030206	CST 030706	2"	1x8	PL-E	>0.60	103x127	78	E27	50
CST 030207	CST 030707	3"	1x12	PL-E	>0.60	118x139	102	E27	50
CST 030208	CST 030708	4"	1x13	PL-E	>0.60	144x150	125	E27	20
CST 030209	CST 030709	5"	1x15	PL-E	>0.60	180x180	162	E27	20
CST 030210	CST 030710	6"	1x18/23	PL-E	>0.60	193x180	170	E27	20