355° IP44

Round LED Down Light



- Optional LED Chip Brands

EPISTAR PHILIPS
OSRAM NICHIA
BRIDGELUX CREE

- Standards

DLC UL LISTED FC SAA CE TÜV GS RoHS



- Application

MEETING HALLS OFFICES
SCHOOLS HOSPITALS
MARKETS HOUSES
STAIRS SHOPPING CENTERS

PRODCT PROFILE

Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
CST_RLDL 0088370	880lm	8W	220–240V	40°	3000K/4000K	Ra≥90









COB >.95 PF 50.000h 220V 240V Voltage



Product Features

- Body of the luminaire is made of aluminium
- Patented heat outlet for long lifespan to optimise maintenance
- High quality COB chips & High luminous efficacy
- 60% - 80% energy saving in relation to halogen& CFL sources
- Replacement to halogen or CFL downlights
- Excellent light spot, comfortable to eyes, no flicker, no strobe.
- Environmental friendly, No UV or IR radiation, no noise.
- High CRI more than 80, approximate to the nature light.

PRODCT PROFILE

Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
CST_SLDL 0088370	880lm	8W	220–240V	40°	3000K/4000K	Ra≥90









COB >.95 PF 50.000h 220V 240V Voltage K CCT



Product Features

- Body of the luminaire is made of aluminium
- Patented heat outlet for long lifespan to optimise maintenance
- High quality COB chips & High luminous efficacy
- 60% - 80% energy saving in relation to halogen& CFL sources
- Replacement to halogen or CFL downlights
- Excellent light spot, comfortable to eyes, no flicker, no strobe.
- Environmental friendly, No UV or IR radiation, no noise.
- High CRI more than 80, approximate to the nature light.