

LED Track Light

PRODCT PROFILE


Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
CST_LTL 2513070/15	2750lm	25W	220–240V	15°	3000K/4000K	Ra⩾90
CST_LTL 2513070/24	2750lm	25W	220–240V	24°	3000K/4000K	Ra⩾90
CST_LTL 2513070/36	2750lm	25W	220–240V	36°	3000K/4000K	Ra⩾90

SMD | >.95 PF | 50.000h | 220V 240V Voltage





Technical Drawing



Optional LED Chip Brands

EPISTAR PHILIPS OSRAM NICHIA BRIDGELUX CREE

Standards

Application

MEETING HALLS, OFFICES, SCHOOLS, HOSPITALS, MARKETS, HOUSES, STAIRS, SHOPPING CENTERS

Product Features

- Body of the luminaire is made of aluminium
- Patented heat outlet for long lifespan to optimise maintenance
- High quality COB chips & High luminous efficacy
- 60% - 80% energy saving in relation to halogen& CFL sources
- Replacement to halogen or CFL downlights
- Excellent light spot, comfortable to eyes, no flicker, no strobe.
- Environmental friendly, No UV or IR radiation, no noise.
- High CRI more than 80, approximate to the nature light.

Photometric Data

