IP44

LED Recessed Spot Light



PRODCT PROFILE

Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
CST_LRSL 30235220	3300lm	30W	220–240V	99°	3000K/4000K	Ra≥90
CST_LRSL 45235220	4950lm	45W	220–240V	99°	3000K/4000K	Ra≥90

COB >.95 PF 50.000h 220V 240V Voltage





Technical Drawing







Optional LED Chip Brands

EPISTAR PHILIPS OSRAM NICHIA BRIDGELUX CREE

Standards

DLC UL FC SAA CE CQC RoHS



PRODCT PROFILE

Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
CST_LRSL 33180172	3630lm	33W	220–240V	68°	3000K/4000K	Ra≥90
CST_LRSL 50215175	5500lm	50W	220–240V	68°	3000K/4000K	Ra≥90

COB >.95 PF 50.000h 220V 240V Voltage

Products Features

- Body of the luminaire is made of aluminium
- Patented heat outlet for long lifespan to optimise maintenance
- High quality COB chips & High luminous efficacy
- 60% - 80% energy saving in relation to halogen& CFL sources
- Replacement to halogen or CFL downlights
- Excellent light spot, comfortable to eyes, no flicker, no strobe.
- Environmental friendly, No UV or IR radiation, no noise.
- High CRI more than 80, approximate to the nature light.

Technical Drawing









Application

